

Craig Street/ Vishal Nayak Abramson Cancer Center University of Pennsylvania





The Problem?

Lack of a **COMMON** genomic identifier in biomedical databases


Results in an **INTEROPERABILITY** problem







The Problem?









Initial Proposal

- ▶ Identify potential genomic identifiers from current ICR projects and potential future use cases
- ▶ Reuse existing CDEs in the caDSR and create new CDEs for these genomic identifiers
- **Each ICR project's data model should utilize at least one or more of these defined CDEs**
- ▶ Additional CDEs may be added to this dynamic list
- ► The Architecture Workspace, Vocabulary/CDE Workspace, and Genome Annotation subject matter experts should oversee the addition of such CDEs







Evolution of the Proposal

>> CBnopesalInGenee, Ribelanid Artificies classes ochehedias one identifier and a appropried dynamic identification than as a genomic identifier itself

cd	Data Model
	Gene
	- Database: char - ID: char - Symbol: char - Name: char
	mRNA
	- Database: char - ID: char
	- NumberofExons: int
	Protein
	- Database: char - ID: char
	- ID. char - MolecularWeight: float








Evolution of the Proposal

<u>Proprtext:</u> Olejec,t-RNAt, anal Propering wish beometric ang phicatical identifier object where one or more approved genomic identifier attributes is instantiated









- Polled Developers of ICR Projects to Determine What Identifiers are Currently Being Used in their Systems
- Compiled List of Required Genomic Identifiers (i.e., DNA or its RNA or Protein Product) based on Survey
- Each ICR Project's Object Model must utilize AT LEAST ONE of these Defined Genomic Identifier CDEs for each UML Class with any Genomic Identifier Attributes.







- If Object Models in the Future Cannot Accommodate one of the Existing CDEs, Additional CDEs may be Added to this Dynamic List.
- To Increase Unification in the Grid, in addition to their Use in UML Models, we Recommend that Applications Accept and Return as Parameters the Defined Genomic Identifier CDEs in their APIs.







List of Recommended Identifiers

- •Ensembl Gene ID
- •Ensembl Transcript ID
- Ensembl Peptide ID
- •Gene GenBank Accession Number
- •mRNA GenBank Accession Number
- •Gene GenBank Accession. Version
- •mRNA GenBank Accession. Version
- Entrez Gene ID
- •RefSeq mRNA Accession Number
- •RefSeq Protein Accession Number
- UniGene Cluster ID
- •UniProtKB Primary Accession Number







Genomic Identifier Property:

- **Define Separate Identifier Term for Genomics Classes**
- Genomic Identifier Imparts more Specificity and Distinguishes from other Type of Identifiers (e.g., patients, tissues, etc.)
- Will be Advantageous when Querying across the Grid -**Defining what Type of Data to Return**
- Provides a Means of Interlinking Various Object Models







An Illustrative Example

The following example shows how one would query disparate object types mapped with the same identifier:

Entrez Gene ID 672 BRCA1: breast cancer 1, early onset

Washington University

CDE-->DEC--->Object Class = Ribonucleic Acid (EVS concept code: C812)

CDE-->DEC--->Class Qualifier = Messenger RNA (EVS concept code: C813)

CDE-->DEC--->Property = Genomic Identifier (EVS concept code: C45766)

CDE-->DEC--->Property Qualifier = Entrez Gene (EVS concept code: C45765)

CDE-->VD--->Syntax constrained to Entrez Gene identifiers, but not enumerated

Georgetown University

CDE-->DEC--->Object Class = Protein (EVS concept code: C17021)

CDE-->DEC--->Class Qualifier = optional (one could specify the protein family)

CDE-->DEC--->Property = Genomic Identifier (EVS concept code: C45766)

CDE-->DEC--->Property Qualifier = Entrez Gene ID (EVS concept code: C45765)

CDE-->VD--->Syntax constrained to Entrez Gene identifiers, but not enumerated









UML Model - Class Diagram

cd Logical Model

Gene

- ensemblgeneID: java.lang.String
- genbankAccession: java.lang.String
- genbankAccession.Version: java.lang.String
- entrezgeneID: java.lang.String
- unigeneclusterID: java.lang.String

MessengerRNA

- ensembltranscriptID: java.lang.String
- genbankAccession: java.lang.String
- genbankAccession.Version: java.lang.StringrefseqID: java.lang.String

Protein

- ensemblpeptideID: java.lang.String
- refseqID: java.lang.String
- uniprotkbPrimaryAccession: java.lang.String







Alternate Modeling Approach

- Specifically Designed for Projects that Cannot Accommodate the Recommended Strategy
- Essentially, this Approach Requires Objects which are "Served Out" and Reference Genes or Gene Products Must Contain an Embedded Identifier.







Genomic Identifier CDE Creation

Current Status

- The Genomic Identifier CDEs have been loaded into the caDSR production server.
- The Data Elements (including the Value Domains) have undergone one round of curation. (courtesy Tommie Curtis, Claire Wolfe, Hong Dang, Craig Street and yours truly.)
- All definitions used have been validated using either an authoritative source or citation.







Genomic Identifier CDE Creation

Current Status

- Reference Documents have been attached to the Genomic **Identifier CDEs.**
- The Genomic Identifier CDEs have undergone an initial review by members of Genome Annotation SIG.
- The CDE creation process has been documented and checked into CVS.

http://cabigcvs.nci.nih.gov/viewcvs/viewcvs.cgi/pir/adopter_penn/month3/Document

ation%20of%20Genomic%20Identifier%20CDEs.doc







Genomic Identifier CDE Creation

Next Steps

- Get the curated Genomic Identifier CDEs reviewed by the VCDE and the members of the Genome Annotation SIG.
- Incorporate gathered feedback.
- Propose the Genomic Identifier CDEs as Candidate Data Standards.







Genomic Identifier CDEs

- Ensembl Gene ID
- •Ensembl Transcript ID
- •Ensembl Peptide ID
- •Gene GenBank Accession Number
- •mRNA GenBank Accession Number
- •Gene GenBank Accession. Version
- •mRNA GenBank Accession. Version
- •Entrez Gene ID
- •RefSeq mRNA Accession Number
- •RefSeq Protein Accession Number
- •UniGene Cluster ID
- •UniProtKB Primary Accession Number







Why Data Standards?

- These data elements are very commonly used within the ICR workspace.
- Promote reuse of the CDEs to ease mapping of the genomic identifiers.
- Prevent post harmonization issues by encouraging developers to harmonize their data elements on these CDEs during the development process.
- Encourage the development of more commonly used CDEs within the ICR workspace as Data Standards.
- Washington University has been funded in Year 2 to create an identifier mapping service based on this list of identifiers, to further support this approach.





